



StoCreativ® Brick

The classic look of brick in a lightweight, energy-efficient cladding.

StoCreativ® Brick is a cost-effective, easy-to-apply decorative wall finish system that can be used over any Sto cladding or other prepared exterior surface including Stucco, EIFS, Tilt-up and CMU to achieve the classic look of brick.

Using self-adhering stencils applied over a primer layer to create the appearance of mortar, this simple finish system offers a sustainable alternative to heavier brick, while avoiding the hassle of dealing with multiple trades and cumbersome accessories.

Available with a variety of brick patterns and color options for both the finish layer and mortar, StoCreativ® Brick is a lightweight, single source system, ideal for new construction and restoration.



StoCreativ® Brick Benefits:

A cost-effective, time-efficient process to achieve the classic look of brick

- Light weight decorative finish system which can reduce costly structural requirements needed for heavier claddings
- Quick and simple application process using self-adhering stencils; doesn't require highly-specialized labor or expensive accessories
- Easy to install even in tight spaces where brick and other heavier claddings just won't work; ideal for restoration of buildings in urban areas
- StoCreativ® Brick is ready to install when you need it; no time wasted waiting for custom colors or special orders

Sustainable, 'single source' system for increased energy-efficiency and greater peace of mind


- StoCreativ® Brick can be installed over any continuous insulation (ci) wall system from Sto, thus providing a proven and hassle-free 'single source' solution to meet ASHRAE design standard 90.1-2010 and the new IGCC/IECC* energy code requirements.
- Light-weight system which creates less solid waste in production and at end-of-life than heavier claddings
- Can be combined with other Sto finishes for multi-cladding aesthetics, thus avoiding the hassle of dealing on the jobsite with multiple suppliers and trades.

Exceptional design versatility


- Wide range of decorative and protective 100% Acrylic wall finishes in virtually unlimited colors
- By varying application technique and finish color combination, StoCreativ® Brick can be used to match any brick veneer texture including aged ones; perfect for building restoration.
- This lightweight wall finish system can also be used to create decorative custom shapes, virtually impossible to achieve with heavy claddings.

*IGCC: International Green Construction Code - IECC: International Energy Conservation Code


Available Brick Patterns




Utility Brick 3/8" (RP)




New York Brick 1/2" (RP)




Used Wall Brick (RP)




Ohio Standard Brick (RP)




Block Pattern (RP)*




Square 8.5 (RP)*



Stack Ribbon Brick (RP)*



Baltimore Brick (RP)*



Herringbone (RP)*

RP: Recycled Plastics

*3 - 4 weeks lead time; Minimum order quantity applies.

Sto New Name	Dimension (inches)		Sheets Per Box	Coverage (Sq. Feet)
	Width x Height x Mortar Joint Width			
Utility Brick 3/8" (RP)	11.5" x 3.625" x .375"		32	480
New York Brick 1/2" (RP)	8" x 2.25" x .5"		47	450
Used Wall Brick (RP)	7.75" x 2.5" x .375"		32	480
Ohio Standard Brick (RP)	7.75" x 2.5" x .375"		32	480
Block Pattern (RP)	8" x 3.75" x .5"		37	480
Square 8.5 (RP)	7 7/8" x 7 7/8" x .5"		37	480
Stack Ribbon Brick (RP)	8" x 3.5" x .5"		32	480
Baltimore Brick (RP)	7.5" x 3.375" x .5"		34	480
Herringbone (RP)	8" x 4" x .5"		48	480

RP: Recycled Plastics

Sto Corp.

3800 Camp Creek Parkway
Building 1400, Suite 120
Atlanta, GA 30331

Phone: 404-346-3666

Toll Free: 1-800-221-2397

Fax: 404-346-3119

www.stocorp.com

5877 03/18

Sto | Building with conscience.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information or proper application, clean-up and mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto. Corp. website, www.stocorp.com.